




DATASHEET

# Sirius Compact Routers

## 12G SDI Compact Video Routers



# SIRIUS COMPACT ROUTERS

## 12G SDI Compact Video Routers

12G video routing for advanced formats and simplified workflows.

The Grass Valley Sirius Compact range is ideally suited to utility routing applications with the ability to route all SDI video formats, including 12G/3G/HD/SD, in matrix sizes from 16x16 to 64x64. These compact routers are controllable from the Sirius Compact Panels, as well as by GV Orbit and the NV9000 control system.



### Key Features

#### Extremely small form factor

- Ultra thin, saves rack space
- 1 RU, 2 RU and 4 RU sizes
- Lightweight design
- Non-square router configurations for monitoring applications

#### Formats

- Future-proof 12G/3G/HD/SD
- DVB-ASI compliant

#### Robust design

- Robust design for rugged conditions
- Highly reliable power supply over 500,000 hours MTBF
- Optional redundant power supply available
- Range operates with the entire Sirius router range

#### Powerful configuration tools

- USB port for configuring IP addresses via AJA's free eMini-Setup software

#### Multiple control capabilities

- Ethernet and serial control
- Up to 8 salvos can be configured and saved in each router
- Standalone and networked control panels
- Graphical User Interface (GUI) panels from GV Orbit or NV9000

### Ordering

#### SCR 1616-12G

##### Sirius Compact Router

16x16 Single Link 12 Gb/s UHD Serial Digital Video Router, 1 RU, 1 power supply provided, redundant is optional

#### SCR 3232-12G

##### Sirius Compact Router

32x32 Single Link 12 Gb/s UHD Serial Digital Video Router, 2 RU, 1 power supply provided, redundant is optional

#### SCR 6464-12G

##### Sirius Compact Router

64x64 Single Link 12 Gb/s UHD Serial Digital Video Router, 4 RU, 1 power supply provided, redundant is optional

#### SCP1

##### Sirius Compact Panel

1 RU Hardware Control Panel for Sirius Compact routers

#### SCP2

##### Sirius Compact Panel

2 RU Hardware Control Panel for Sirius Compact routers

#### SCRPS2A

Sirius CR6464-12G +12 VDC power supply, for redundant operation or spare

#### CRPS1

Redundant power supply for Compact Routers – to be used as the redundant or spare supply for the SCR 1616-12 and the SCR 3232-12G compact routers.

# SCR 1616-12G

## Sirius Compact Router



SCR 1616-12G offers increased capacity for larger configurations while maintaining a compact 1 RU profile with support for 1.5G-SDI/3G-SDI/6G-SDI/12G-SDI with 16x 12G-SDI inputs and 16x 12G-SDI outputs.

Sirius 12G SDI routers support large format resolutions, high frame rate (HFR) and deep color formats, while reducing cable runs when transporting 4K UHD over SDI. The routers offer network-based and/or physical control, with a new USB port for configuring IP addresses via AJA's eMini-Setup software. SCR 1616-12G is the ideal choice for any situation where a balance of size and capacity are critical such as mid-sized post facilities and mobile trucks.

### SCR 1616-12G Sirius Compact Router Rear

**RS-422**  
RS-422 remote control via 9-pin D-connector with basic support for Grass Valley Native Protocol support

**LAN Connection**  
RJ-45 10/100/1000 LAN Connector – internal web server, Bonjour support

**USB Connection**  
USB port to easily configure the router IP address and simplify network configurations

**Fully Redundant AC Power Supplies**  
Two independent 12 VDC inputs provide safe operations. Power status can be checked from a LAN-attached browser

**Reference Input with Loop-through**  
The reference input synchronizes the router switching point per SMPTE specifications. The reference input supports blackburst for SD and tri-level sync for HD

**SD-SDI/HD/3G/6G/12G Inputs and Outputs**  
SMPTE ST 259/292/424/2081/2082

## Specifications

### Video Format

270 Mb/s, 1.5 Gb/s, 3 Gb/s, 6 Gb/s, 12 Gb/s SDI  
270 Mb/s DVB-ASI  
Format agnostic, 270 Mb/s – 12 Gb/s

### Video Input Digital

12G-SDI inputs  
16x 12G-SDI BNC, SMPTE ST 259/292/424/2081/2082

### Video Output Digital

12G-SDI outputs  
16x 12G-SDI BNC, SMPTE ST 259/292/424/2081/2082  
Noninverting

### Ancillary Data

Passes all SDI embedded ancillary data including audio

### Salvo

Up to 8 salvos can be configured and saved in each Sirius router

### Cable Equalization (Belden 1694A)

- 12 Gb/s, up to 55m
- 6 Gb/s, up to 110m
- 3 Gb/s, up to 185m
- 1.5 Gb/s, up to 210m
- 270 Mb/s, up to 405m
- Automatic operation

### Reclocking

270 Mb/s, 1.483 Gb/s, 1.485 Gb/s, 2.967 Gb/s, 2.970 Gb/s, 5.934 Gb/s, 5.940 Gb/s, 11.868 Gb/s, 11.880 Gb/s – Auto Select

All other rates are passed through and not reclocked

### Switching Modes

Single, Dual, and Quad link modes  
Switches in vertical blanking per SMPTE RP 168

### Control Panel Compatibility

SCP1 – 1 RU X-Y Ethernet control panel  
SCP2 – 2 RU X-Y Ethernet control panel

### Reference Input

External, 2x BNC  
Looping, nonterminating  
Blackburst or tri-level sync

### Network Interface

1x RJ-45, 10/100/1000 Ethernet  
Supports Sirius Ethernet control panels, direct connect or networked  
Basic support for Grass Valley Native Protocol  
Embedded web server for remote control

### USB Interface

1x Mini-USB for IP configuration using eMini-Setup

### Serial Interface

1x DB-9 Female, RS-422  
Basic support for Grass Valley Native Protocol  
9-pin D-connector pinout is as follows:

1	GND
2	TX-
3	RX+
4	GND
5	No Connection
6	GND
7	TX+
8	RX-
9	GND
Shell	GND

### Dimensions (WxDxH)

1 RU – 441.96 x 39.12 x 44.45 mm (17.4 x 1.54 x 1.75 in.)

### Weight

0.7 kg (1.4 lbs.)

### Power

10–14 VDC regulated, 16W typ, 18W max, power supply required, included with purchase

**AC adapter:** 100–240 VAC, 50/60 Hz, universal input

### Environmental

**Safe operating temperature:** 0 to 40°C (32 to 104°F)

**Safe storage temperature (Power OFF):** -40 to 60°C (-40 to 140°F)

**Operating relative humidity:** 10–90% noncondensing

**Operating altitude:** <3,000m (<10,000 ft.)

# SCR 3232-12G

## Sirius Compact Router



SCR 3232-12G offers increased capacity for larger configurations while maintaining a compact 2 RU profile with support for 1.5G-SDI/3G-SDI/6G-SDI/12G-SDI with 32x 12G-SDI inputs and 32x 12G-SDI outputs.

Sirius 12G-SDI routers support large format resolutions, high frame rate (HFR) and deep color formats, while reducing cable runs when transporting 4K UHD over SDI. The routers offer network-based and/or physical control with a new USB port for configuring IP addresses via AJA's eMini-Setup software.

SCR 3232-12G is the ideal choice for any situation where a balance of size and capacity are critical such as mid-sized post facilities and mobile trucks.

### SCR 3232-12G Sirius Compact Router Rear

**RS-422**  
RS-422 remote control via 9-pin D-connector with basic support for Grass Valley Native Protocol support

**LAN Connection**  
RJ-45 10/100/1000 LAN Connector – internal web server, Bonjour support

**USB Connection**  
USB port to easily configure the router IP address and simplify network configurations

**Fully Redundant AC Power Supplies**  
Two independent 12 VDC inputs provide safe operations. Power status can be checked from a LAN-attached browser

**Reference Input with Loop-through**  
The reference input synchronizes the router switching point per SMPTE specifications. The reference in/out supports blackburst for SD and tri-level sync for HD

**SD-SDI/HD/3G/6G/12G Inputs and Outputs**  
SMPTE ST 259/292/424/2081/2082

## Specifications

### Video Format

270 Mb/s, 1.5 Gb/s, 3 Gb/s, 6 Gb/s, 12 Gb/s SDI  
270 Mb/s DVB-ASI  
Format agnostic, 270 Mb/s – 12 Gb/s

### Video Input Digital

12G-SDI inputs  
32x 12G-SDI BNC, SMPTE ST 259/292/424/2081/2082

### Video Output Digital

12G-SDI outputs  
32x 12G-SDI BNC, SMPTE ST 259/292/424/2081/2082  
Noninverting

### Ancillary Data

Passes all SDI embedded ancillary data including audio

### Salvo

Up to 8 salvos can be configured and saved in each Sirius router

### Cable Equalization (Belden 1694A)

- 12 Gb/s, up to 50m
- 6 Gb/s, up to 100m
- 3 Gb/s, up to 170m
- 1.5 Gb/s, up to 200m
- 270 Mb/s, up to 390m
- Automatic operation

### Reclocking

270 Mb/s, 1.483 Gb/s, 1.485 Gb/s, 2.967 Gb/s, 2.970 Gb/s, 5.934 Gb/s, 5.940 Gb/s, 11.868 Gb/s, 11.880 Gb/s – Auto Select  
All other rates are passed through and not reclocked

### Switching Modes

Single, Dual, and Quad link modes  
Switches in vertical blanking per SMPTE RP 168

### Control Panel Compatibility

SCP1 – 1 RU X-Y Ethernet control panel  
SCP2 – 2 RU X-Y Ethernet control panel

### Reference Input

External, 2x BNC  
Looping, nonterminating  
Blackburst or tri-level sync

### Network Interface

1x RJ-45, 10/100/1000 Ethernet  
Supports Sirius Ethernet control panels, direct connect or networked  
Basic support for Grass Valley Native Protocol  
Embedded web server for remote control

### USB Interface

1x Mini-USB for IP configuration using eMini-Setup

### Serial Interface

1x DB-9 Female, RS-422  
Basic support for Grass Valley Native Protocol  
9-pin D-connector pinout is as follows:

1	GND
2	TX-
3	RX+
4	GND
5	No Connection
6	GND
7	TX+
8	RX-
9	GND
Shell	GND

### Weight

4.6 lb (2.1 kg)

### Dimensions (WxDxH)

2 RU – 441.96 x 39.12 x 88.9 mm (17.4 x 1.54 x 3.50 in.)

### Power

10-14 VDC regulated, 24W typ, 25.2W max, power supply required, included with purchase

**AC adapter:** 100-240VAC, 50/60 Hz, universal input

### Environmental

**Safe operating temperature:** 0 to 40°C (32 to 104°F)

**Safe storage temperature (Power OFF):** -40 to 60°C (-40 to 140°F)

**Operating relative humidity:** 10-90% noncondensing

**Operating altitude:** <3,000m (<10,000 ft.)

# SCR 6464-12G

## Sirius Compact Router



SCR 6464-12G offers increased capacity for larger configurations while maintaining a compact 4 RU profile with support for 1.5G-SDI/3G-SDI/6G-SDI/12G-SDI/with 64x 12G-SDI inputs and 64x 12G-SDI outputs.

Sirius 12G-SDI routers support large format resolutions, high frame rate (HFR) and deep color formats while reducing cable runs when transporting 4K UHD over a single SDI link. Multilink gang control also offers routing of up to 8K resolutions. The router offers network-based and physical control with a USB port for configuring IP addresses via AJA's free eMini-Setup software.

SCR 6464-12G is the ideal choice for any situation where a balance of size, performance and capacity are critical such as post facilities and mobile trucks.

### SCR 6464-12G Sirius Compact Router Rear

#### Fully Redundant AC Power Supplies


Two independent 12 VDC inputs provide safe operations. Power status can be checked from a LAN-attached browser

#### Reference Input with Loop-through

The reference input synchronizes the router switching point per SMPTE specifications. The reference input supports blackburst for SD and tri-level sync for HD

#### LAN Connection

RJ-45 10/100/1000 LAN Connector - internal web server, Bonjour support



#### RS-422

RS-422 remote control via 9-pin D-connector with basic support for Grass Valley Native Protocol support

#### USB Connection

USB port to easily configure the router IP address and simplify network configurations

#### SD-SDI/HD/3G/6G/12G Inputs and Outputs

SMPTE ST 259/292/424/2081/2082

## Specifications

### Video Format

270 Mb/s, 1.5 Gb/s, 3 Gb/s, 6 Gb/s, 12 Gb/s SDI

270 Mb/s DVB-ASI

Format agnostic, 270 Mb/s – 12 Gb/s

### Video Input Digital

12G-SDI inputs

64x 12G-SDI BNC, SMPTE ST 259/292/424/2081/2082

### Video Output Digital

12G-SDI outputs

64x 12G-SDI BNC, SMPTE ST 259/292/424/2081/2082

Noninverting

### Ancillary Data

Passes all SDI embedded ancillary data including audio

### Salvo

Up to 8 salvos can be configured and saved in each Sirius router

### Cable Equalization (Belden 1694A)

– 12 Gb/s, up to 50m

– 6 Gb/s, up to 90m

– 3 Gb/s, up to 180m

– 1.5 Gb/s, up to 210m

– 270 Mb/s, up to 390m

– Automatic operation

### Reclocking

270 Mb/s, 1.483 Gb/s, 1.485 Gb/s, 2.967 Gb/s, 2.970 Gb/s, 5.934 Gb/s, 5.940 Gb/s, 11.868 Gb/s, 11.880 Gb/s – Auto Select

All other rates are passed through and not reclocked

### Switching Modes

Single, Dual, and Quad link modes

Switches in vertical blanking per SMPTE RP 168

### Control Panel Compatibility

SCP1 (first 32 I/O in Normal, all I/O in Dual or Quad mode) – 1 RU X-Y Ethernet control panel

SCP2 (Single, Dual or Quad mode) – 2 RU X-Y Ethernet control panel

### Reference Input

External, 2x BNC

Looping, nonterminating

Blackburst or tri-level sync

### Network Interface

1x RJ-45, 10/100/1000 Ethernet

Supports Sirius Ethernet control panels, direct connect or networked

Basic support for Grass Valley Native Protocol

Embedded web server for remote

### USB Interface

1x Mini-USB for IP configuration using eMini-Setup

### Serial Interface

1x DB-9 Female, RS-422

Basic support for Grass Valley Native Protocol

9-pin D-connector pinout is as follows:

1	GND
2	TX-
3	RX+
4	GND
5	No Connection
6	GND
7	TX+
8	RX-
9	GND
Shell	GND

### Dimensions (WxDxH)

4 RU – 441.96 x 39.37 x 177.8 mm (17.4 x 1.55 x 7.00 in.)

### Weight

4.2 kg (9.2 lbs.)

### Power

10-14 VDC regulated, power supply required, included with purchase

**AC adapter:** 100-240 VAC, 50/60 Hz, universal input

### Environmental

**Safe operating temperature:** 0 to 40°C (32 to 104°F)

**Safe storage temperature (Power OFF):** -40 to 60°C (-40 to 140°F)

**Operating relative humidity:** 10-90% noncondensing

**Operating altitude:** <3,000m (<10,000 ft.)

# SCP2

## Sirius Compact Panel

### 2 RU Hardware Control Panel for Sirius Compact Routers



SCP2 is a 2 RU control panel that can be used in standalone or networked configurations suitable for all Sirius routers including the SCR 6464-12G. Connecting via Ethernet to the same network as Sirius routers, SCP2 enables full control from any location without the need for a computer. Up to four Sirius routers can be controlled from a single control panel. Supports ganged

dual and quad port routing, allowing users to group together multiple inputs and outputs for Dual Link, 4K and UHD workflows. In addition to HD and SD, every Sirius can route two or four grouped 3G-SDI connections, supporting uncompressed or RAW 4K and UHD signals.

### Specifications

#### User Interface

- 80 buttons with removable overcap for lens chips
- Includes factory installed lens chip set
- High and low button tally indication, configurable brightness
- Controls up to four Sirius routers
- Panel lock feature
- Destination lock feature

#### Router Support

- SCR 1616-12G
- SCR 3232-12G
- SCR 6464-12G

#### Salvo

8 salvos buttons can be enabled to trigger a Sirius router's configured salvos

#### Network Interface

- 1x RJ-45, 10/100/1000 Ethernet
- Embedded web server for remote control

#### USB Interface

1x Mini-USB for IP configuration using eMini-Setup

#### Dimensions (WxDxH)

2 RU – 441.96 x 33.02 x 88.9 mm (17.4 x 1.3 x 3.5 in.)

#### Weight

1.0 kg (2.1 lbs.)

#### Power

10-14 VDC regulated, 4W typical, 9.6W max, power supply required, included with purchase  
**AC adapter:** 100-240 VAC, 50/60 Hz, universal input

#### Environmental

- Safe operating temperature:** 0 to 40°C (32 to 104°F)
- Safe storage temperature (Power OFF):** -40 to 60°C (-40 to 140°F)
- Operating relative humidity:** 10-90% noncondensing
- Operating altitude:** <3,000m (<10,000 ft.)



# SCP1 Sirius Compact Panel



## 1 RU Hardware Control Panel for Sirius Compact Routers

SCP1 is an optional 1 RU control panel that can be used in standalone or networked configurations, suitable for all Sirius routers except the SCR 6464-12G. (For SCR 6464-12G, please see the SCP2.) Connecting via Ethernet to the same network as Sirius routers, SCP1 enables full control from any location without the need for a computer. Up to four Sirius routers can be controlled from a single control

panel. Supports ganged dual and quad port routing, allowing users to group together multiple inputs and outputs for Dual Link, 4K and UHD workflows. In addition to SD and HD, every Sirius panel can route two or four grouped 3G SDI connections, supporting uncompressed or RAW 4K and UHD signals.

### Specifications

#### User Interface

40 buttons with removable overcap for lens chips  
Includes factory installed lens chip set  
High and low button tally indication, configurable brightness  
Controls up to four Sirius routers  
Panel lock feature  
Destination lock feature

#### Router Support

SCR 1616-12G  
SCR 3232-12G

#### Network Interface

1x RJ-45, 10/100/1000 Ethernet  
Embedded web server for remote control

#### USB Interface

1x Mini-USB for IP configuration using eMini-Setup

#### Dimensions (WxDxG)

1 RU – 441.96 x 33.02 x 44.45 mm (17.4 x 1.3 x 1.75 in.)

#### Weight

0.6 kg (1.2 lbs.)

#### Power

10-14 VDC regulated, 2.5W typical, 6W max, power supply required, included with purchase  
**AC adapter:** 100-240 VAC, 50/60 Hz, universal input

#### Environmental

**Safe operating temperature:** 0 to 40°C (32 to 104°F)  
**Safe storage temperature (Power OFF):** -40 to 60°C (-40 to 140°F)  
**Operating relative humidity:** 10-90% noncondensing  
**Operating altitude:** <3,000m (<10,000 ft.)



This product may be protected by one or more patents. For further information, please visit: [www.grassvalley.com/patents](http://www.grassvalley.com/patents)

DS-PUB-3-1006A-EN

Grass Valley®, GV® and the Grass Valley logo are trademarks or registered trademarks of Grass Valley USA, LLC, or its affiliated companies in the United States and other jurisdictions. Grass Valley products listed above are trademarks or registered trademarks of Grass Valley USA, LLC or its affiliated companies, and other parties may also have trademark rights in other terms used herein. Copyright © 2021-2022 Grass Valley Canada. All rights reserved. Specifications subject to change without notice.

[www.grassvalley.com](http://www.grassvalley.com) Join the Conversation at GrassValleyLive on [Facebook](#), [Twitter](#), [YouTube](#) and Grass Valley on [LinkedIn](#)